

PICHON



NEW RANGE



COMPACT LOADERS FROM 26 TO 60 HP

TECHNICAL SPECIFICATIONS

SERIE	26.26 SERIE		29.26 SERIE				29.34 SERIE				34.50 SERIE				45.60 SERIE		
MODEL	26.26 R	29.26 R	29.26 F	29.26 K	29.26 C	29.34 R	29.34 F	29.34 K	29.34 C	34.50 R	34.50 F	34.50 K	34.50 C	45.60 F	45.60 K	45.60 C	
Protection	ROPS Frame		ROPS Frame	ROPS/FOPS Frame	ROPS/FOPS Canopy	ROPS/FOPS Cab	ROPS Frame	ROPS/FOPS Frame	ROPS/FOPS Canopy	ROPS/FOPS Cab	ROPS Frame	ROPS/FOPS Frame	ROPS/FOPS Canopy	ROPS/FOPS Cab	ROPS/FOPS Frame	ROPS/FOPS Canopy	ROPS/FOPS Cab
Axles	Rigid		Rigid				Planetary gear reducers with limited slip differential										
ENGINE																	
Type	C1.1 CATERPILLAR®		C1.1 CATERPILLAR®				C1.5 CATERPILLAR®				C2.2 CATERPILLAR®				C2.2 TURBO CATERPILLAR®		
Max power / Stage	19,1 kW (26 HP) / III A		19,1 kW (26 HP) / III A				25,1 kW (34 HP) / III A				36,3 kW (50 HP) / III A				44,5 kW (60 HP) - III A (Flex)		
Cylinder	1 130 cm³		1 130 cm³				1 500 cm³				2 200 cm³				2 216 cm³		
Speed	0-12 km/h		0-15 km/h				0/20 km/h				0/7 km/h (work) 0/20 km/h				0/25 km/h (automatic)		
Tank capacity: gazole	30 L		50 L				50 L				50 L				60 L		
Tank capacity: oil	35 L		50 L				50 L				50 L				60 L		
ELECTRIC SYSTEM																	
Voltage - Battery	12V - 60Ah		12V - 60Ah				12V - 60Ah				12V - 70Ah				12V - 70Ah		
HYDRAULIC SYSTEM																	
Transmission	Hydrostatic		Hydrostatic				Hydrostatic				Hydrostatic				Hydrostatic		
Hydraulic pressure	260 bar		340 bar				340 bar				340 bar				420 bar		
Work hydraulic	42 L/min - 180 bar		42 L/min - 180 bar				48 L/min - 180 bar				66 L/min - 180 bar				89 L/min - 200 bar		
WEIGHT/LOAD CAPACITY																	
Tipping load in straight position (non articulated machine and horizontal lifting arm)	800 kg		1300 kg				1400 kg				1500 kg				3200 kg		
Tipping load in straight position (articulated machine and horizontal lifting arm)	650 kg		1000 kg				1100 kg				1200 kg				2700 kg		

DIMENSIONS

	26.26 SERIE	29.26 SERIE 29.34 SERIE	34.50 SERIE	45.60 SERIE
A	1420 mm	1400 mm	1720 mm	2100 mm
B	841 mm	1165 mm	1185 mm	1435 mm
C	2898 mm	3105 mm	3940 mm	4450 mm
G	2600 mm	2900 mm	3400 mm	4500 mm
L	1750 mm	1815 mm	1885 mm	-
M	2081 mm	2480 mm	2545 mm	2515 mm
N	893 mm	1380 mm	1590 mm	1500 mm
O	55°	40°	40°	45°
P	900/1300 mm	1100/1300 mm	1350/1550 mm	1900/2200 mm
Q	1863 mm	2180 mm	2868 mm	3550 mm



ZI DE LAVALLOT - B.P. 21 - 29490 GUIPAVAS - FRANCE
 TEL: +33 2 98 344 100 - Email: info@pichonindustries.com

www.pichonindustries.com

